



Section G

Cable Assemblies

| Part # | Description | Feet | Leadhead |
|----------|-----------------|------|----------------|
| 513-3545 | 4/0 Black Cable | 9 | 180° One End |
| 513-3559 | 4/0 Black Cable | 10 | 90° Both Ends |
| 513-3557 | 4/0 Black Cable | 10 | 180° Both Ends |
| 513-3530 | 4/0 Red Cable | 6 | 180° One End |
| 513-3550 | 4/0 Red Cable | 8 | 180° One End |
| 513-3544 | 4/0 Red Cable | 9 | 180° One End |
| 513-3558 | 4/0 Red Cable | 10 | 90° Both Ends |
| 513-3556 | 4/0 Red Cable | 10 | 180° Both Ends |

Cable Size Reference Chart

| <u>Cable Size</u> |
|-------------------|
| # 4 |
| # 2 |
| # 1 |
| 1/0 |
| 2/0 |
| 3/0 |
| 4/0 |
| 250 MCM |

| <u>Amp. Hours Capacity</u> |
|----------------------------|
| 0-150 A.H. |
| 151-374 A.H. |
| 375-510 A.H. |
| 511-680 A.H. |
| 681-850 A.H. |
| 851-1040 A.H. |
| 1041-1500 A.H. |
| 1501-Over A.H. |